


## 2925. TRILLINGSDEMPER MET TAILLE TYPE 2

Afwijkende diameter, hoogte, shore hardheid of draad op aanvraag leverbaar.

Standaard ook in RVS (A2 / A4) leverbaar.

Ook leverbaar in diverse andere materialen zie volgende link [materiaalspecificaties](#)



| Artikelcode          | D  | d   | H  | G   | Lengte | G   | Materiaal     |
|----------------------|----|-----|----|-----|--------|-----|---------------|
| 2925.01000803006.045 | 10 | 4,5 | 8  | M 3 | 6      | M 3 | NR 55° St. 37 |
| 2925.01001004010.080 | 10 | 8   | 10 | M 4 | 10     | M 4 | NR 55° St. 37 |
| 2925.01501504010.085 | 15 | 8,5 | 15 | M 4 | 10     | M 4 | NR 55° St. 37 |
| 2925.01501504010.120 | 15 | 12  | 15 | M 4 | 10     | M 4 | NR 55° St. 37 |
| 2925.02001504010.140 | 20 | 14  | 15 | M 4 | 10     | M 4 | NR 55° St. 37 |
| 2925.02001906018.140 | 20 | 14  | 19 | M 6 | 18     | M 6 | NR 55° St. 37 |
| 2925.02001906018.144 | 20 | 14  | 19 | M 6 | 18     | M 6 | NR 40° St. 37 |
| 2925.02003004010.140 | 20 | 14  | 30 | M 4 | 10     | M 4 | NR 55° St. 37 |
| 2925.02003006018.120 | 20 | 12  | 30 | M 6 | 18     | M 6 | NR 55° St. 37 |
| 2925.02502008023.180 | 25 | 18  | 20 | M 8 | 23     | M 8 | NR 55° St. 37 |
| 2925.03002006008.220 | 30 | 22  | 20 | M 6 | 8      | M 6 | NR 55° St. 37 |
| 2925.03002006008.226 | 30 | 22  | 20 | M 6 | 8      | M 6 | NR 65° St. 37 |
| 2925.03002006008.228 | 30 | 22  | 20 | M 6 | 8      | M 6 | NR 80° St. 37 |
| 2925.03002006008.229 | 30 | 22  | 20 | M 6 | 8      | M 6 | NR 90° St. 37 |
| 2925.03002008023.220 | 30 | 22  | 20 | M 8 | 23     | M 8 | NR 55° St. 37 |
| 2925.03002008023.250 | 30 | 25  | 20 | M 8 | 23     | M 8 | NR 55° St. 37 |
| 2925.03002506015.180 | 30 | 18  | 25 | M 6 | 15     | M 6 | NR 55° St. 37 |
| 2925.04003008023.250 | 40 | 25  | 30 | M 8 | 23     | M 8 | NR 55° St. 37 |
| 2925.04003008023.330 | 40 | 33  | 30 | M 8 | 23     | M 8 | NR 55° St. 37 |
| 2925.04004808023.200 | 40 | 20  | 48 | M 8 | 23     | M 8 | NR 55° St. 37 |
| 2925.04004808023.205 | 40 | 20  | 48 | M 8 | 23     | M 8 | NR 40° RVS A2 |
| 2925.04602510028.400 | 46 | 40  | 25 | M10 | 28     | M10 | NR 55° St. 37 |

| Artikelcode          | D  | d  | H  | G   | Lengte | G   | Materiaal |        |
|----------------------|----|----|----|-----|--------|-----|-----------|--------|
| 2925.05003010028.420 | 50 | 42 | 30 | M10 | 28     | M10 | NR 55°    | St. 37 |
| 2925.05504508015.440 | 55 | 44 | 45 | M 8 | 15     | M 8 | NR 55°    | St. 37 |
| 2925.05504508028.440 | 55 | 44 | 45 | M 8 | 28     | M 8 | NR 55°    | St. 37 |
| 2925.05704410028.250 | 57 | 25 | 44 | M10 | 28     | M10 | NR 55°    | St. 37 |
| 2925.05704410028.450 | 57 | 45 | 44 | M10 | 28     | M10 | NR 55°    | St. 37 |
| 2925.05704508020.250 | 57 | 25 | 45 | M 8 | 20     | M 8 | NR 55°    | St. 37 |
| 2925.05704510028.440 | 57 | 44 | 45 | M10 | 28     | M10 | NR 55°    | St. 37 |
| 2925.06006010028.490 | 60 | 49 | 60 | M10 | 28     | M10 | NR 55°    | St. 37 |
| 2925.07005312028.450 | 70 | 45 | 53 | M12 | 28     | M12 | NR 55°    | St. 37 |
| 2925.09507516041.800 | 95 | 80 | 75 | M16 | 41     | M16 | NR 55°    | St. 37 |